

HYDRO PNEUMATIC SYSTEM



Owing to our countable experience of the industry, we have been able to integrate supply and install a range of Hydro Pneumatic Systems. Congruent with industry laid guidelines, these systems are available in various specifications and also in customized range to meet the specific needs of the customers. Our teams make use of advanced machines and high grade material procured from the reliable vendors in the market in manufacture them.

HYDRO PNEUMATIC SYSTEM

SALIENT FEATURES

www.marssolaraqua360.com

- Tough ABS construction
- Wear-résistance shaft and impeller
- Excellent cooling of the motor enables the pump to operate even when it is partially submerged
- Automatic operation with start/stop float switch and manual operation
- Supplied with manpower plug and self-seal fitting
- Protection IP 68

SPECIFICATIONS

Power Range Single Phase: 1.0 HP – 3.0 HP

Three Phase: 7.0 HP – 87 HP

Speed 3950 rpm

Versions A.C. Single Phase 220 V, 230 V

A.C. Three Phase 460 V, 465 V

Type of Duty S1 (Continuous)

Degree of Protection IP 68

Insulation Class B / F

Impeller Type Vortex / Closed

Single Channel / Closed Multi

• Channel / Open Single Channel

Motor Type Dry (Rewindable)

PH Value 6 To 12

Head Maximum upto 247 ft

Maximum flow upto 2500 US gpm

Liquid Viscosity 1 mm / S

Liquid Density 1kg/dm

Maximum Liqiuid Temperature 104 F

Delivery Size 2 1/2 To 6



APPLICATIONS













MARS SOLAR AQUA 360 PVT LTD

68 - 70, KCR Business Today, F3-01, 3rd Floor, 7th Street, Tatabad, Coimbatore, Tamilnadu - 641 012, Tel: 0422 2495360, Mobile: 94870 36000, 94860 36000, 94890 36000

E-Mail: info@marssolaraqua360.com